

Flow Iron Pup Joints

Reliable pup joints for well service applications

 **Working pressure:**
15,000 psi [103 MPa]

 **Sizes:**
2 or 3 in

Applications

Hydraulic fracturing, cementing, well testing, and flowback

How it improves wells

Flow iron pup joints from Cameron deliver maximum total lifecycle cost savings, even in the oil and gas industry's most demanding applications. For all of your flow iron requirements, from high-stage-count hydraulic fracturing to cementing, well testing, and even abrasive flowback, you can count on Cameron for high reliability and low cost.

Additional information

Cameron offers flow iron pup joints in standard 2- and 3-in sizes and lengths from 2 to 10 ft with 1502 hammer wing unions and nonpressure seal threads (NPST).



Cameron 2-in pup joint.

Flow Iron Pup Joint Specifications

Size, in	Length, ft	Threads	Hammer Union	Style	Bore Diameter, in	Working Pressure, psi
2	4	NPST	1502	Nondetachable	1.72	15,000
2	6	NPST	1502	Nondetachable	1.72	15,000
2	8	NPST	1502	Nondetachable	1.72	15,000
2	8	NPST	1502	Detachable nut	1.72	15,000
2	10	NPST	1502	Nondetachable	1.72	15,000
2	10	NPST	1502	Detachable nut	1.72	15,000
3	2	NPST	1502	Nondetachable	2.59	15,000
3	2	NPST	1502	Detachable nut	2.59	15,000
3	3	NPST	1502	Nondetachable	2.59	15,000
3	4	NPST	1502	Nondetachable	2.59	15,000
3	4	NPST	1502	Detachable nut	2.59	15,000
3	8	NPST	1502	Nondetachable	2.59	15,000
3	8	NPST	1502	Detachable nut	2.59	15,000

All specifications are subject to change without notice.